

PRODUCTS & APPLICATION

A series

[A series \(/en.php/product/detail?id=49\)](/en.php/product/detail?id=49)

[FA series \(/en.php/product/detail?id=50\)](/en.php/product/detail?id=50)

[F series \(/en.php/product/detail?id=51\)](/en.php/product/detail?id=51)

A series

SWT/A series

The locking method of SWT/A series is three-point locking, with thickness the same with that of the F-type nut. Its feature is axial three-point locking and is applicable for special environment.

Material: 42CrMo,45#, 40Cr

Hardness: HRC28°—32°

Thread Precision: ISO4H

Run Out: 0.005mm

请您留言

Thread	D	h	n-g	t	d	n-m	MAX.Nm
SWT/A M12x1.25P	26	14	3-3	2	22	2-M4	3.5

SWT/A M14x1.5P	30	14	3—4	2	26	2—M4	3.5
SWT/A M15x1.0P	30	14	3—4	2	26	2—M4	3.5
SWT/A M16x1.5P	30	14	3—4	2	26	2—M4	3.5
SWT/A M17x1.0P	32	16	3—4	2	28	2—M4	3.5
SWT/A M18x1.5P	32	16	3—4	2	28	3—M4	3.5
SWT/A M20x1.0P	38	16	3—4	2	34	3—M4	3.5
SWT/A M20x1.5P	38	16	3—4	2	34	3—M4	3.5
SWT/A M22x1.5P	38	16	3—4	2	34	3—M4	3.5
SWT/A M24x1.5P	38	18	3—5	2	34	3—M4	3.5
SWT/A M25x1.5P	38	18	3—5	2	34	3—M4	3.5
SWT/A M27x1.5P	40	18	3—5	2	36	3—M4	3.5
SWT/A M30x1.5P	45	18	3—5	2	41	3—M4	3.5
SWT/A M33x1.5P	50	18	3—5	2	46	3—M4	3.5
SWT/A M35x1.5P	52	18	3—5	2	48	3—M6	8
SWT/A M36x1.5P	52	18	3—5	2	48	3—M6	8
SWT/A M39x1.5P	58	20	3—6	2.5	53	3—M6	8
SWT/A M40x1.5P	58	20	3—6	2.5	53	3—M6	8
SWT/A M42x1.5P	62	20	3—6	2.5	57	3—M6	8
SWT/A M45x1.5P	65	20	3—6	2.5	60	3—M6	8
SWT/A M48x1.5P	70	20	3—6	2.5	65	3—M6	8
SWT/A M50x1.5P	70	20	3—6	2.5	65	3—M6	8
SWT/A M50x2.0P	70	20	3—6	2.5	65	3—M6	8
SWT/A M52x1.5P	73	22	3—7	3	67	3—M6	8
SWT/A M55x2.0P	75	22	3—7	3	69	3—M6	8
SWT/A M56x2.0P	75	22	3—7	3	69	3—M6	8
SWT/A M60x2.0P	80	22	3—7	3	74	3—M6	8
SWT/A M64x2.0P	85	22	3—7	3	79	3—M6	8
SWT/A M65x2.0P	85	22	3—7	3	79	3—M6	8
SWT/A M68x2.0P	92	24	3—8	3.5	85	3—M8	18
SWT/A M70x2.0P	92	24	3—8	3.5	85	3—M8	18
SWT/A M72x2.0P	94	24	3—8	3.5	87	3—M8	18
SWT/A M75x2.0P	98	24	3—8	3.5	91	3—M8	18
SWT/A M76x2.0P	98	24	3—8	3.5	91	3—M8	18
SWT/A M80x2.0P	105	24	4—8	3.5	98	3—M8	18
SWT/A M85x2.0P	110	24	4—8	3.5	103	3—M8	18
SWT/A M90x2.0P	120	26	4—10	4	112	3—M8	18

Remark: (1) The above data is just provided for reference, Jiangsu Swift Machinery Technology Co.,Ltd reserves the right to revise it.(2) 1NM=10.2kgf.cm=0.73lb.ft (3) Non-standard nut can be customized.

Spindle Lock nut Bearing block Wedge block Rotary table Hydraulic lock nut Accessory

A Xuzhuang Park Road, Xingren Town, Tongzhou District, Nantong, Jiangsu, China
T +86-513-86222888 F +86-513-85650761

About Us

Company Profile
(/en.php/about/index)

Company History
(/en.php/about/history)

请您留言

Product

Product Line
(/en.php/product/cate?id=28)
Application Fields
(/en.php/product/app-list)

Company Strength

Solution
(/en.php/tech/solution?type=1)
Technical Innovation
(/en.php/tech/innovation)

Contact Us

Careers
(/en.php/contact/job)
Location
(/en.php/contact/index)

9/23/2017

Product Line

Honors and Rewards

FAQ

</en.php/about/honor>

</en.php/tech/qanda>

Copyright(C)2009-2017 Jiangsu Swift Machinery Technology Co., Ltd 苏ICP备17027845号-1 (<http://www.miitbeian.gov.cn/publish/query/indexFirst.action>)

DESIGN BY **HANSNBRAND** (<http://hansnbrand.com>)

请您留言

<http://www.ntswift.com/en.php/product/detail?id=49>

3/3